

KM-1790

Direct Drive, High-speed, 2-needle, Needle Feed Split Needle Bar Machine with an Automatic Thread Trimmer



Code	Lubrication Type		Code	Application	Code	Hook	Code	Trimming
O M	Micro Lubrication Type	Dry Head	F	Foundation	None	Standard Hook	None	None-Trimming
1	Auto Lubrication Type		G	General materials	L	Large Hook	7	Trimming

Specification

Model	KM-1790		KM-1791
	MG	MBL	BL
Application	General	Heavy	
Lubrication	Micro Lubrication		Auto Lubrication
Max. Sewing Speed	3,000 spm		
Max. Stitch Length	5 mm	7 mm	
Engage or Disengage the Needle Bar	Split Needle Bar		
Needle Bar Stroke	33.4 mm		
Thread Take-Up Stroke	52 mm	64.6 mm	
Height of Feed Dog	1 mm		
Height of Presser Foot Lifter	7 mm(by Hand) / 15 mm(by Knee) / 13 mm(by Automatic)		
Hook	Standard	Large Hook	
Needle (DPX5)	#11-#16(#16)	#14-#22(#22)	
Sewing Area	257 mm(Width), 120 mm(Height), 87 mm(Arm Jaw)		
Bed Size	518 mm × 178 mm		
Bobbin Thread Winder	Built-in the Machine Head (Upper Arm part)		
Automatic Back-tack Device	Provided		
Automatic Trimming Device	Provided		
Motor	AC Servo Motor(550W)		
Power	1-Phase (100-240V), 3-Phase (200-240V, 50/60Hz)		

Option Gauge (Standard Spec.:1/4")

Model	Spec	3/32"	1/8"	5/32"	3/16"	7/32"	1/4"	5/16"	7/16"	1/2"	5/8"
		2.4mm	3.2mm	4mm	4.8mm	5.6mm	6.4mm	7.9mm	11mm	12.7mm	15.9mm
KM-1790		<input type="radio"/>									
KM-1790BL		<input type="radio"/>									

Application

A needle feed sewing machine that is completely free from unevenness in material feed and material puckering, suitable to fancy stitching for jeans, vinyl or leather, etc.

*Specifications and appearance are subject to change for the improvement of products without prior notice.

SunStar SUNSTAR MACHINERY CO., LTD.

TRADE OFFICE

178-212, G AJWA - DONG, SED - KU, INCHEON KOREA
TEL : (82-32) 580-5740 ~60 FAX : (82-32) 584-3025 ~6

WEB-SITE

<http://www.sunstar.co.kr>

E-MAIL

sunstar@sunstar.co.kr
fortuna@sunstar.co.kr

OVERSEAS NETWORK

SUNSTAR MACHINERY (SHANGHAI) CO., LTD.
TEL : 86 21 6957 6311 FAX : 86 21 6957 6312
SUNSTAR MACHINERY (SHANGHAI) CO., LTD. SHANGHAI BRANCH
TEL : 86 21 6353 2233 FAX : 86 21 6353 8640
SUNSTAR QINGDAO BRANCH
TEL : 86 532 482 2236 FAX : 86 532 481 1262
SUNSTAR NANJING BRANCH
TEL : 86 25 464 7389 FAX : 86 25 464 7389
SUNSTAR HANGZHOU BRANCH
TEL : 86 571 8704 4709 FAX : 86 571 8601 6046

OVERSEAS NETWORK

SUNSTAR TIANJIN BRANCH
TEL : 86 22 2445 8882 FAX : 86 22 2445 2400
SUNSTAR HONGKONG LTD.
TEL : 852 2729 707 FAX : 852 2729 7573
SUNSTAR GUANGDONG BRANCH
TEL : 86 769 249 1610 FAX : 86 769 234 4042
SUNSTAR FUJIAN BRANCH
TEL : 86 595 8859 8871 FAX : 86 595 8859 8872
SUNSTAR U.S.A INC.
TEL : 1 305 591 9596 FAX : 1 305 591 0661
SUNSTAR HOCHIMINH BRANCH OFFICE
TEL : 84 8 811 0302 FAX : 84 8 811 4588
SUNSTAR HANOI BRANCH OFFICE
TEL : 84 4 734 0268 FAX : 84 4 734 0278
SUNSTAR NEW DELHI OFFICE
TEL : 91 124 280 3006 FAX : 91 124 280 3007
SUNSTAR JAKARTA BRANCH OFFICE
TEL : 62 21 4586 5839 FAX : 62 21 4586 5840
SUNSTAR MACHINERY(SINGAPORE)
TEL : 008 65 6341 5015 FAX : 008 65 6341 5016

AGENT:

Direct Drive, High-speed, 2-needle, Needle Feed Split Needle Bar
Lock Stitch Machine with an Automatic Thread Trimmer

KM-1790 Series



KM-1790 Series

New, High-speed Twin Needle Sewing Machine Series D The Advanced Technology of SunStar!

Combining Fortuna IV AC Servo Motor automatic thread motor with new high-speed twin needle sewing machine series, in which new various functions are integrated to be used conveniently, we have completely applied high-tech mechatronics to sewing machine. This would contribute to enhance quality of sewing pattern and productivity.




Direct Drive



Equipped with 550W AC Servo Motor, the sewing machine can powerfully handle heavy materials.

Compared with competitors, more stable motor capability is offered (patent filing under way) Based on 3-D CAD & CAE interpretation, it produces less noises and low vibration. The sewing machine can make accurate stop, and its prompt and smooth responsiveness leads to productivity enhancement.




Developed Through



>> Enlarged Working Space

Wider working space leads to productivity elevation.



>> Dry Head Lubrication


Dry Head Type is classified into SEMI-DRY and MICRO LUBRICATION TYPE to minimize risk of polluting sewing material, and special coating is applied to main parts to enhance endurance and wear resistance.




- The blades carry out horizontal movement so that they are not subject to readjustment when the needle distance changes, since it can cut any types of thread regardless of its thickness. The trimmer blades which have wide operating section can be easily assembled or disassembled.




- The thread adjusting device is able to control the tension of left and right upper threads separately. In any conditions, clean and high-quality sewing is guaranteed.



► Automatic-Lubrication Type



► Semi-dry Type
The oil circulation system involving oil tank is used to supply oil through hook only. Oil has been completely removed from the needle bar and the thread take-up.



► Micro-Lubrication Type
The oil tank supplies oil to hook with the oil circulation method. Very tiny volume of oil is provided to needle bar, enhancing productivity and minimizing the sewing material tainting



Engage or Disengage the Needle Bar

With simple button mechanism for disengaging the left or right needle bar, which enables the operator to engage or disengage the needle bars.



Thread remaining in the bobbin can be verified easily through inspection windows installed on the left and right sides of each board.

Owing to the fitting of a large hook, double quantity of lower threads can be secured promoting work efficiency (BL type) compared to normal hook.