

SPEC.



	ST-C	UT-B	5
	Upper Thread Trimming(Cylinder Bed)(Option)	Lower Thread Trimming(Air Pressure 3)	FOMEL THESAM THILLING AND TRESOURE T

Device

PK	TL	띧	₽	ATF	VK2	¥ K1	픎	8	
Needle Thread Clamp	Compact Spot Light	See Through Light for Hemming	Attaching Guide for Elastic Lace	Tape Feeder(Side meter type)	Walking Presser Foot(Covering)	Walking Presser Foot(Hemming)	Hemming Guide	Covering Guide	Attachment(Option)

DEVICE

Specification	
Model	SC 7300
Stitch Type	ISO 406, 407, 602, 605
Application	General sewing for knit
Sewing Speed	Max. 6000 spm (4000 spm at the time of Shipment)
Ctitch Longth	

Model		SC 7300
Application	General sewing for knit	
Sewing Speed	Max. 6000 spm (4000 spm at the time of Shipment)	time of Shipment)
Stitch Length	1.4~3.6 mm	
Needle	UY 128GAS #65 ~ #90	
Needle Space	2-needle	3.2, 4.0, 4.8, 5.6, 6.4 mm
To the state of th	3-needle	5.6, 6.4 mm
Needle Stroke	31 mm (SC 7300H: 33 mm)	
Height of Presser Foot	Max. 7 mm (when Top cover thread is used, up to 5 mm)	ead is used, up to 5 mm)
Circumference of Cylinder Bed	270 mm	
Differential Ratio	Max. Normal Differential Ratio	1: 2.9
	Max. Reverse Differential Ratio	1: 0.3
Lubrication	Automatic lubrication	

SunStar. SUNSTAR MACHINERY CO., LTD.

http://www.sunstar.co.kr	WEB-SITE	#178-212, GAJWA - DONG, SEO - KU, INCHEON, KOREA TEL : $(82-32)580-5740\sim 60$ FAX : $(82-32)584-3025\sim 6$	TRADE OFFICE
sunstar@sunstar.co.kr fortuna@sunstar.co.kr	E-MAIL)- KU, INCHEON, KOREA FAX: (82-32)584-3025∼6	OFFICE

OVERSEAS NETWORK

SUNSTAR MACHINERY (SHANGHAI) CO.,LTD. FAX: 86 21 6957 6312 TE: 186 21 6857 6312 SUNSTAR MACHINERY (SHANGHAI) CO.,LTD. SHANGHAI BRANCH FAX: 86 21 6353 2233 FAX: 86 21 6353 2233 SUNSTAR AUNIQUAD BRANCH FAX: 86 532 481 1262 SUNSTAR AUNIQUAD BRANCH FAX: 86 532 481 1262 SUNSTAR AUNIQUAD BRANCH FAX: 86 532 487 7389 FAX: 86 25 464 7389 SUNSTAR HANGZHOU BRANCH FEL : 86 571 8704 4709

SUNSTAR TIANJIN BRANCH
TEL: 86:22 2445 8882
SUNSTAR HONGKONG LTD.
TEL: 88:22 279 7078
SUNSTAR GUANGDONG BRANCH
TEL: 86:592 8871
TEL: 86:592 8871
TEL: 86:592 8871
SUNSTAR FUJIAN BRANCH
TEL: 86:592 891 8506
FAX: 88
SUNSTAR FUJIAN BRANCH
TEL: 305:591 8506
FAX: 88
SUNSTAR U.S.A INC.
TEL: 1305:591 8506
FAX: 81

SUNSTAR HOCHIMINH BRANCH OFFICE TEL: 84.8 811 0302
SUNSTAR HANDI BRANCH OFFICE TEL: 84.4 734 0268
SUNSTAR NEW DELHI OFFICE TEL: 91 124.280 3006
SUNSTAR JAKARTA BRANCH OFFICE TEL: 62.21 4584 5317

High-speed Cylinder Bed 3-Needle Interlock Sewing Machine



00 Series

New high-speed cylinder bed interlock sewing machine, embodiment of years High-speed Cylinder Bed 3-Needle Interlock Sewing Machine of technical know-how of SunStar

newly developed a chain sewing machine. Applied with high-technology, it has practical design and can In addition, with Fortuna III/IV installed, it realizes perfect mechatronics. be easily assembled. It is more durable and user friendly Leveraging 30 years of cumulative expertise from lock-stitch sewing machines manufacturing, SunStar has

lent Quality

ncredible Sewing

Enables stale and accurate control by excellent feed system, you can get even and beautiful stitch in various sewing materials.

Easy to Use



Ease-of-use covers

saved. Their appearance designs are also simplified Covers are designed to make them easy to use, so that threading time can be

Optimized for High-Speed Seaming



Enhanced knee lift function
The knee lifter is designed to be simple and convenient to use. The height of the presser foot can be adjusted without opening the top cover.



Small diameter cylinder bedThe cylinder bed diameter is small, making various sewing works possible. (270 mm) This mechanism prevents oil from leaking at bed The oil in the cylinder is returned to the oil fan. Cylinder Oil Return Structure

and sewing materials from being tainted.



Embedded Location Detector

motor and makes sure exact location detection. It has a simplified design. The location detector is embedded in pulley. It accurately monitors the signals from servo



Oil Cooling Fan System

This system can also enhance product durability could lower oil viscosity. An oil cooling fan is installed at the lower shaft to prevent oil temperature rise and to ensure stable oil supply. High-speed sewing causes heat, which



Ta1

Small Motor(Optional)

simpler. It uses timing belt instead of V-belt. Since controlled by Fortuna IV, it can The types of motor used can be chosen as an option. If a small motor is installed, it makes the installation of sewing machine



change simply according to

thread take up lever cam can easy maintenance. Also, Looper thread easy to remove and the bed side makes looper

use purpose.

Cam which locate on top of

thread take up lever cam

Easy maintenance of Looper

maintain more stable working conditions.

achievement of better stitch quality.

and delicately adjusted. It enables proper handling of diverse sewing materials and the

The tension of needle thread can be individually Delicate adjustment of thread tension